



**MULTIPLASTICS (EUROPE) Limited**

**Multiplastics (Europe) Ltd.**  
Columbus House,  
30 Manchester Road,  
Northwich, Cheshire.  
CW9 5ND

Tel: +44 (0) 1606 330011  
Fax: +44 (0) 1606 331990  
sales@multiplastics.co.uk  
www.multiplastics.co.uk



Certificate Number 7877  
ISO 9001



# SRP2800T

## Silicone Transfer Tape

**SRP2800T** is a Transfer tape with an adhesive carrying, silicone coated bleached Kraft paper; by using a two side silicone coating the material is self-wound without an integral backing liner, this makes it ideal for applications where single spindles are used. This products has been specifically designed for use on envelopes and business forms.

### Features

- Converts well on all makes and models of machines and at all speeds
- Extra strong adhesive grip for high content security
- Clean running with no adhesive creep
- Can be pre-printed for “point of sale” advantages

### Typical Applications

- Envelope “Peel and Seal” applications
- Integrated label backing

### Grades Available

- Finger lift or Flush edge
- Single wound or Bobbin wound

### General Information

- Handling and Product Health and Safety details available on request
- Recommended storage in dry conditions between 30 °C and 5 °C
- Best used within 6 months of manufacture



**MULTIPLASTICS (EUROPE) Limited**

**Multiplastics (Europe) Ltd.**  
Columbus House,  
30 Manchester Road,  
Northwich, Cheshire.  
CW9 5ND

Tel: +44 (0) 1606 330011  
Fax: +44 (0) 1606 331990  
sales@multiplastics.co.uk  
www.multiplastics.co.uk



Certificate Number 7877  
ISO 9001



## Typical Properties

| Properties        | Unit            | Value        |
|-------------------|-----------------|--------------|
| Adhesive          | Hot Melt Rubber | 35 gsm       |
| Liner             | Bleached White  | 55 gsm       |
| Thickness         | Liner           | 0.055mm      |
|                   | Adhesive        | 0.030mm      |
|                   | Total           | 0.090mm      |
| Peel strength     | N/M             | Steel = 1200 |
| Loop Tack         | N/M             | 1000         |
| Shear             | Per kilo        | >100 hrs     |
| Temperature range | °C              | -20 to + 60  |
| Shelf life        |                 | 12 months    |

As all applications are subject to those conditions prevailing within specific applications, we recommend that a test be carried out to your satisfaction prior to full production.

The information and data contained in this document are given in good faith and supersede those given in any previous version. No liability, warranty or guarantee of final product performance is created by this document. No freedom from any patent is granted or to be inferred. This document does not constitute as a sales specification.

December 2015